

Chest freezer LT C200



- Low cost of ownership
- Limited maintenance
- On-site service

- Easily installable & movable
- Efficient cyclopentane insulation
- ISO 9001, 14001 & 45001 Certified

Specifications	
Technical	
Gross volume	198 litres
Net volume	189 litres
Temp. range	-25°C to -45°C
Temp. probes	1/PTC
Compressor	Embraco
Baskets (incl./optional)	1/6
Refrigerant	R 290
Noise level	55 dB
Power consumption 24/h	2,8 kWh
Power consumption	1.022 kWh / year
Voltage	230V
Frequency	50 Hz
Features	
Audible & visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Connection for remote alarm	Optional
Material	
Inner	Precoated white steel
Outer	Galvanized pre-coated steel
Dimensions	
Height (with castors)	885 mm
Width	923 mm
Depth (incl. condenser)	630 mm
Depth (incl. condenser & handle)	680 mm
Net weight	63 kg
Internal dimensions	
Height	635/385 mm
Width	755/550 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

LT C200

Product no. N111006

Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6	3	18	N311200
	11	9	99	N311220
			= 117	
75 mm	4	3	12	N311300
	8	9	72	N311320
			= 84	
100 mm	3	3	9	N311400
	5	9	45	N311420
			= 54	